Uncertainties Caused by Resistances in Evapotranspiration Estimation Using High-Density Eddy Covariance Measurements

WEN LI ZHAO,^{a,b} GUO YU QIU,^a YU JIU XIONG,^{c,d} KYAW THA PAW U,^d
PIERRE GENTINE,^b AND BAO YU CHEN^c

^a School of Environment and Energy, Peking University Shenzhen Graduate School, Peking University, Shenzhen, China

^b Department of Earth and Environmental Engineering, Columbia University, New York, New York

^c School of Civil Engineering, Sun Yat-Sen University, Guangzhou, China

^d Department of Land, Air and Water Resources, University of California, Davis, Davis, California

^e Research Institute of Agricultural Resources and Environment, Jilin Academy of Agricultural Sciences, Key Laboratory of Plant Nutrition and Agro-Environment in Northeast Region, Ministry of Agriculture, Changchun, Jilin, China

(Manuscript received 24 August 2019, in final form 30 April 2020)

ABSTRACT

Quantifying the uncertainties caused by resistance parameterizations is fundamental for understanding, improving, and developing terrestrial evapotranspiration (ET) models. Using high-density eddy covariance (EC) tower observations in a heterogeneous oasis in northwest China, this study evaluates the impacts of resistances on the estimation of latent heat flux (LE), the energy equivalent of ET, by comparing resistance parameterizations with different complexities under one- and two-source Penman–Monteith (PM) equations. The results showed that the mean absolute percent error (MAPE) for the LE estimates from the one- and two-source PM equations varied from 32% to 53%, and the uncertainties were caused mainly by the resistance parameterizations. Calibrating the parameters required in the resistance estimations could improve the performance of the PM equations; specifically, the MAPEs for the one-source PM equations were approximately 16%, whereas they were 38% for the two-source PM equations, emphasizing that multiple resistances result in increased uncertainties. The following conclusions were reached: 1) the empirical and biophysical parameters required in resistance estimations were responsible for the uncertainty; 2) increasingly complex resistance parameterizations resulted in greater uncertainties in LE estimates; and 3) models without resistance parameterizations exhibited reduced uncertainties in LE estimates.

1. Introduction

The Penman–Monteith (PM) equation (Monteith 1965), which is considered to adequately represent the evapotranspiration (ET) process, is one of the preeminent and most extensively used techniques for estimating ET (Allen et al. 1998; Mallick et al. 2014; Ershadi et al. 2015). However, the accurate estimation of terrestrial ET with the PM equation is challenged substantially by inaccuracies in the parameterizations associated with the resistance terms (e.g., Liu et al. 2012; Wang and Dickinson 2012; Zhang et al. 2016; Mallick et al. 2018a,b; Sullivan et al. 2019) that are used to describe the

combined effects of stressors, such as water stress and stomatal closure. The resistance terms can refer to both canopy resistance and aerodynamic resistance in a one-source model (Wang and Dickinson 2012); in addition, these terms can refer to a more complicated resistance network that includes surface resistance, canopy bulk stomatal resistance, and other sources of resistance in a so-called multilayer/multisource model, such as those described in Shuttleworth and Gurney (1990), Norman et al. (1995), Zhang et al. (2016), and Deng et al. (2017).

The resistances cannot be measured directly at or beyond the canopy scale and thus are often indirectly estimated. The aerodynamic resistance r_a is often estimated using the Monin–Obukhov similarity theory (MOST), where the accuracy of the estimate depends on parameters such as the roughness length for heat (or momentum) transfer and atmospheric stratification (Huang et al. 2016; Rigden et al. 2018; Gerhards et al. 2019). For canopy resistance, its inverse, namely, canopy conductance,

Supplemental information related to this paper is available at the Journals Online website: <https://doi.org/10.1175/JHM-D-19-0191.s1>.

Corresponding author: Yu Jiu Xiong, xiongyuj@mail.sysu.edu.cn

is often estimated based on leaf stomatal conductance g_s (Baldocchi et al. 1991; Leuning et al. 1995; Zhang et al. 2011; Rodrigues et al. 2016) using empirical or physical models with varying degrees of complexity, such as the Jarvis–Stewart framework (Jarvis 1976; Stewart 1988; Mu et al. 2007; Zhang et al. 2010; Tan et al. 2019) or the Ball–Berry framework (Ball et al. 1987; Medlyn et al. 2011; Morillas et al. 2013; Jefferson 2017). Compared to calculating r_a , estimating canopy resistance is more problematic because the leaf-level g_s is commonly measured at small scales in situ (e.g., Irmak et al. 2008; Zhang et al. 2011) or in the laboratory under controlled conditions (e.g., Ball et al. 1987; Tyree et al. 2005), and these environments do not capture the spatiotemporal variations in the land surface and atmospheric conditions (Irmak et al. 2008; Franks et al. 2017). Additionally, g_s values for plant species under different water and climatic combinations are scarce. Moreover, current leaf-level models fail to capture the complex biological controls on water and carbon fluxes throughout the canopy and landscape (Damour et al. 2010; Matheny et al. 2014; Mallick et al. 2015, 2016; van Dijk et al. 2015; Buckley 2017; Bhattarai et al. 2018; Franks et al. 2018) and may contain empirical functions that need to be calibrated prior to application. However, the calibration process is sensitive to the different variables and requires field observations, which are unavailable in most cases.

In addition to the uncertainties generated by the resistance parameterizations, one-source models are suitable for short and dense canopies or bare soil surfaces (e.g., Shuttleworth and Wallace 1985; Rana and Katerji 1998), and uncertainties in ET estimates can be caused by the big-leaf assumption for sparse or tall canopies (Ershadi et al. 2015). Therefore, a two-source model structure has been proposed to better represent the energy and water flux exchanges among the soil, vegetation, and atmosphere via a network of resistances configured architecturally either in series or in parallel (e.g., Shuttleworth and Wallace 1985; Norman et al. 1995; Boulet et al. 2015; Yao et al. 2017a; Y. Li et al. 2019; X. Li et al. 2019). Although the soil and canopy resistances are separately estimated using methods similar to those used in the one-source models, additional hypotheses are introduced to represent two-source conditions, introducing more model complexity. However, a more complex model is likely more difficult to parameterize and apply than a simpler model. As a consequence, the accurate estimation of ET requires an in-depth identification of the sources of uncertainty (Long et al. 2014; Ershadi et al. 2015; Zhang et al. 2016; Yao et al. 2017b; Mallick et al. 2018a,b; Gerhards et al. 2019). Therefore, the objectives of this study are threefold: 1) to evaluate the uncertainties caused by resistances in ET

estimates by employing one- and two-source PM models with different parameterizations and complexities, 2) to identify the sources of uncertainty in resistance parameterizations, and 3) to discuss possible solutions for reducing such uncertainties.

The remainder of this paper is organized as follows. We first describe the study methods, including the resistance models, study sites, and datasets (section 2). Then, in section 3, we present the results regarding resistance-related uncertainties in ET estimates with different degrees of complexity under one- and two-source conditions. We then discuss possible solutions in section 4. The abbreviations and variables used in this study are listed in Table A1 in the appendix.

2. Methods and datasets

a. Study framework

To assess the impacts of resistances on the estimation of ET [hereby represented by the latent heat flux (LE), ET's energy equivalent], we evaluated these influences under one- and two-source networks for the PM equation (Fig. 1). We simplified the evaluation by focusing on r_s and neglecting the uncertainty caused by r_a because considerable uncertainty will be generated if r_a is improperly parameterized (Liu et al. 2007; Mallick et al. 2018b).

For the one-source PM equation [Eq. (1)], r_s is estimated using the empirical Jarvis–Stewart framework, which links canopy resistance to the leaf-level g_s and environmental stress functions (Jarvis 1976; Stewart 1988), because this framework is one of the most widely used methods (Damour et al. 2010). Furthermore, this approach will continue to be used in estimating resistance (Buckley 2017), as no single method is currently available to estimate resistances accurately (Matheny et al. 2014; van Dijk et al. 2015; Mallick et al. 2016; Bhattarai et al. 2018). Although different versions of stress functions exist for the Jarvis–Stewart framework, the functions in Eq. (3) (PM_JA) were adopted here because the functions have been tested and have performed well in arid northwest China, including our study area and an adjacent experimental site consisting of maize (e.g., S. Li et al. 2013; Li et al. 2015; Hu and Jia 2015). Moreover, the empirical method of Katerji and Perrier (1983) (abbreviated PM_KP), which requires fewer empirical variables than the PM_JA model and has been calibrated at the abovementioned experimental maize site (Li et al. 2015), was included.

For the two-source PM model, the algorithms proposed by Mu et al. (2007) (abbreviated PM_Mu) and Zhang et al. (2009, 2010) (abbreviated PM_PLSH) were used.

FIG. 1. A schematic showing the workflow and scientific questions addressed in this study. Note that this study focuses on canopy resistance (black boxes), and complexity is defined as the number of empirical (or biophysical) variables required in the canopy resistance parameterization (see section 2a for details).

In PM_Mu, canopy resistance is estimated using the leaf area index (LAI)-based Jarvis-Stewart framework with stress functions associated with the air temperature and vapor-pressure deficit (VPD) [Eq. (13)] (Mu et al. 2007), whereas canopy resistance is calculated based on the normalized vegetation difference index (NDVI) in PM_PLSH [Eq. (15)] (Zhang et al. 2009, 2010). This difference in the canopy resistance parameterization is beneficial for investigating the impact of the parameterization on the ET estimation. Additionally, the uncertainties caused by resistance parameterizations from the empirical PM_KP method to the phenomenological Jarvis-Stewart framework with increasing complexity (defined as the number of empirical variables required for parameterizing the canopy resistance) are also discussed.

b. Study area and evaluation data

The study area is the Zhangye Oasis in the middle of the Heihe River basin (Fig. 2), and it is located at 100°6′–100°52′E and 38°32′–39°24′N, Gansu Province, northwest China. The mean annual air temperature, precipitation, and pan evaporation are 7.3°C, 100–250 mm, and 1200–1800 mm, respectively. The elevations of the oasis and the adjacent Gobi Desert range from 1400 to 1600 m, and the area is generally flat. Maize, spring wheat, vegetables, orchards, and residential areas are the main land-use types in the oasis (Fig. 2).

The datasets consisted of daytime observations from 17 flux towers deployed inside the oasis over an area covering 5.5 km × 5.5 km from May to September 2012; the data were provided by the Heihe Watershed Allied Telemetry Experimental Research (HiWATER) project (X. Li et al. 2013; Liu et al. 2018). At each flux tower site, both an eddy covariance (EC) system (LI-COR Co., Ltd.)

and an automatic weather station (AWS) (Campbell Co., Ltd.) with sampling frequencies of 10 Hz and 10 min, respectively, were installed [see Table S1 in the online supplemental material and Liu et al. (2016) for details]. Of the 17 EC systems, 14 were placed in maize fields while the other 3 were installed in a vegetable field, a residential area, and an orchard. The HiWATER project provided quality-controlled LE values every 30 min, and these data were processed by a research group (Liu et al. 2016). If the energy balance closure rate [i.e., $(LE + H)/(R_n - G)$] was less than 0.8, the LE from the HiWATER project was forcibly changed to achieve closure using the Bowen ratio method (Twine et al. 2000), which has been used extensively (e.g., Barr et al. 2006; Liu et al. 2011; Xu et al. 2013).

The LAI was measured by an LAI-2000 instrument (LI-COR Co., Ltd.) in a 5 m × 5 m vegetated area near each EC system (Qu et al. 2014). Twenty measurements were collected during the HiWATER project, but LAI values were unavailable for most sites on several days. Ultimately, 16 days of LAI measurements, representing the seedling, shooting, heading, filling, and maturity stages of maize, were used in this study. The LAI values for the maize sites are shown in Fig. 3a, and the weather conditions corresponding to the LAI measurement are shown in Fig. 3b.

c. Model and resistance parameterization descriptions

1) ONE-SOURCE PM EQUATION

The one-source PM equation is as follows (Monteith 1965):

FIG. 2. Study area: (a) locations of the Zhangye Oasis and the Heihe River basin in China, (b) 21 EC flux towers in the HiWATER project, and (c) detailed locations of the 17 EC systems within the key experimental area in the Zhangye Oasis. The figure is modified from Y. Q. Wang et al. (2016). AWS and LAS are abbreviations for automatic weather station and large-aperture scintillometer, respectively.

$$L(ET) = \frac{\Delta A + \rho_a C_p VPD/r_a}{\Delta + \gamma(1 + r_s/r_a)}. \quad (1)$$

Parameter r_a was calculated, neglecting the effect of atmospheric stability, using Eq. (2) (Brutsaert and Stricker 1979; Irmak et al. 2008):

$$r_a = \frac{\ln[(z_r - d)/z_{om}] \ln[(z_r - d)/z_{oh}]}{k^2 u_{zr}}, \quad (2)$$

where k is von Kármán's constant ($k = 0.4$); d is the zero-plane displacement height and commonly taken as $2/3$ of the vegetation height; z_{om} is the local surface roughness length for momentum transport (in meters) and assumed to be 0.13 times the vegetation height; and z_{oh} is the local surface roughness for heat (in meters) and assumed to be equal to $0.1z_{om}$ (Brutsaert and Stricker 1979).

(i) r_s parameterization in PM_JA

Parameter r_s in Eq. (1) was estimated using the Jarvis–Stewart framework:

$$r_s = \frac{r_{smin}}{LAI[f(R_s)f(VPD)f(T_a)f(\theta)]}, \quad (3)$$

where r_{smin} is the minimum stomatal resistance under optimal conditions (i.e., none of the controlling variables

are limiting), and the following stress functions that have performed well in the study area (e.g., S. Li et al. 2013; Li et al. 2015; Hu and Jia 2015; Bai et al. 2017, 2019) were used:

$$f(R_s) = \frac{R_s(1000 + k_1)}{1000(R_s + k_1)}, \quad (4a)$$

$$f(VPD) = 1 - k_2 VPD, \quad (4b)$$

$$f(T_a) = \frac{(T_a - T_L)(T_H - T_a)^t}{(T_{op} - T_L)(T_H - T_{op})^t}, \quad \text{where}$$

$$t = \frac{T_H - T_{op}}{T_{op} - T_L}, \quad \text{and} \quad (4c)$$

$$f(\theta) = \frac{\theta - \theta_w}{\theta_f - \theta_w}. \quad (4d)$$

(ii) r_s parameterization in PM_KP

In the PM_KP model, r_s is expressed as follows:

$$r_s = c_1 r^* + c_2 r_a, \quad (5)$$

where c_1 and c_2 are empirical coefficients, and r^* is related to climatic variables:

FIG. 3. (a) Variations in the average leaf area index (LAI) from 14 maize fields in the 2012 growing season and (b) box-and-whisker plots for solar radiation (Rs), air temperature (Ta), relative humidity (RH), and wind speed (u) for the days corresponding to panel a using daytime (0700–1900 UTC + 8) data from the 15th EC tower. The error bars in (a) indicate the standard deviations of the observations. In the box-and-whisker plot, the boxes show the interquartile range (25th–75th percentiles), the dashed line through a box represents the median, and the white and gray dots represent the mean and outlier values, respectively.

$$r^* = \frac{\Delta + \gamma}{\Delta \gamma} \times \frac{\rho_a C_p \text{VPD}}{(R_n - G)}. \quad (6)$$

In Eq. (1) the available energy, equaling the difference between net radiation and soil heat flux, was obtained directly from the flux tower observations, whereas the VPD, psychrometric constant, and slope of the saturation vapor-pressure curve were indirectly estimated from meteorological observations according to FAO paper 56 (Allen et al. 1998). The determination of the empirical coefficients (e.g., c_1 and c_2) and biophysical values (e.g., $r_{s\min}$ and T_{op}) required in the r_s parameterization [Eqs. (3)–(5)] is listed in Table 1 in section 2c(3).

2) TWO-SOURCE PM EQUATION

In the PM_Mu (Mu et al. 2007) and PM_PLSH (Zhang et al. 2009, 2010) algorithms, total ET is regarded as the sum of canopy transpiration E_c and soil evaporation E_s as follows:

$$L(\text{ET}) = \text{LE}_s + \text{LE}_c, \quad (7)$$

where LE_s is estimated by combining a modified PM equation with the complementary relationship theory

according to Mu et al. (2007) and Zhang et al. (2009, 2010):

$$\text{LE}_s = \frac{\Delta \times A_s + \rho_a \times C_p \times \text{VPD}/r_{a,s}}{\Delta + \gamma(1 + r_{s,s}/r_{a,s})} \times \left(\frac{\text{Rh}}{100}\right)^{\text{VPD}/\beta}, \quad (8)$$

where the surface resistance of the soil surface $r_{s,s}$ and aerodynamic resistance $r_{a,s}$ are estimated as follows:

$$r_{s,s} = r_{\text{tot}} \times r_{\text{corr}}, \quad (9a)$$

$$r_{\text{corr}} = \frac{1}{\frac{101300}{P} \times \left(\frac{T_a + 273.15}{293.15}\right)}, \quad (9b)$$

where r_{tot} is the uncorrected total aerodynamic resistance, which is assumed to be constant based on the biome type (Table 1):

$$r_{a,s} = \frac{r_{sc} \times r_{ss}}{r_{sc} + r_{ss}}, \quad (10a)$$

$$r_{sc} = \frac{1}{\text{gl}_{\text{sh}}}, \quad \text{and} \quad (10b)$$

TABLE 1. Biophysical parameters used for the resistance parameterizations.

Resistance method		Variables	Precalibrated values ^a			Calibrated values ^b
			Orchard	Vegetable	Maize	Maize
Empirical	PM_KP	c_1	0.85	0.85	0.85	0.60
		c_2	1.83	1.83	1.83	−0.31
Jarvis–Stewart framework	PM_JA	r_{smin} (s m ^{−1})	20	20	20	49.07
		k_1 (W m ^{−2})	5	5	5	10.00
		k_2 (hPa ^{−1})	0.023	0.023	0.023	0.024
		T_L (°C)	5	5	5	15.73
		T_{op} (°C)	35	35	35	38.51
		T_H (°C)	55	55	55	56.82
	PM_Mu	Tmin_open (°C)	8.61	12.02	12.02	13.36
		Tmin_close (°C)	−8.00	−8.00	−8.00	2.00
		VPD_close (Pa)	4300	4200	4500	4208
		VPD_open (Pa)	650	650	650	328
	PM_PLSH	c_L (m s ^{−1})	0.0065	0.007	0.007	0.003
		b1 (mm s ^{−1})	0.412	0.138	0.138	5.43
		b2 (mm s ^{−1})	4.118	2.5	2.5	0.79
		b3	8	5.8	5.8	2.13
		b4 (mm s ^{−1})	−0.2208	−0.3792	−0.3792	−0.16
		VPD_close (Pa)	3700	3800	3800	4155.2
		VPD_open (Pa)	650	650	650	614.8
		Topt (°C)	10	20	20	34.90
		k_3 (°C)	30	30	30	15.20

^a The precalibrated values were directly cited from the literature, i.e., PM_KP and PM_JA from Li et al. (2015), PM_Mu from Mu et al. (2007), and PM_PLSH from Zhang et al. (2009), whereas the calibrated values were deduced from the observed LE data in this study and the inverse PM equation through a least squares method [see section 2c(3) for details].

^b Calibration was performed for the maize sites because only one EC system each was applied for the orchard and vegetable areas and the observations were limited.

$$r_{ss} = \frac{\rho C_p}{4\sigma T_a^3}. \quad (10c)$$

the inverse of canopy conductance g_c and described separately in PM_Mu and PM_PLSH:

A brief introduction to LE_c is provided below:

$$r_{s,c} = 1/g_c. \quad (12)$$

$$LE_c = \frac{\Delta \times A_c + \rho_a \times C_p \times VPD/r_{a,c}}{\Delta + \gamma(1 + r_{s,c}/r_{a,c})}, \quad (11)$$

(i) $r_{s,c}$ parameterization in PM_Mu

In PM_Mu, g_c is estimated as follows:

$$g_c = LAI \times c_L \times m(Tmin) \times m(VPD), \quad (13)$$

where $r_{a,c}$ is assumed to be equal to $r_{a,s}$ and estimated using Eq. (10) (Zhang et al. 2009, 2010), whereas $r_{s,c}$ is

$$m(Tmin) = \begin{cases} 1.0, & Tmin \geq Tmin_open \\ \frac{Tmin - Tmin_close}{Tmin_open - Tmin_close}, & Tmin_close < Tmin < Tmin_open, \\ 0.1, & Tmin \leq Tmin_close \end{cases} \quad (14a)$$

$$m(VPD) = \begin{cases} 1.0, & VPD \leq VPD_open \\ \frac{VPD_close - VPD}{VPD_close - VPD_open}, & VPD_close < VPD < VPD_open. \\ 0.1, & VPD \geq VPD_close \end{cases} \quad (14b)$$

(ii) $r_{s,c}$ parameterization in PM_PLSH

$$g_0 = 1/[b_1 + b_2 \times \exp(-b_3 \times \text{NDVI})] + b_4, \quad (16a)$$

$$g_c = g_0(\text{NDVI}) \times m(T_{\text{day}}) \times m(\text{VPD}), \quad (15)$$

$$m(T_{\text{day}}) = \begin{cases} 0.01, & T_{\text{day}} \geq T_{\text{close_max}} \\ \exp\left[-\left(\frac{T_{\text{day}} - T_{\text{opt}}}{k_3}\right)^2\right], & T_{\text{close_min}} < T_{\text{day}} < T_{\text{close_max}} \\ 0.01, & T_{\text{day}} \leq T_{\text{close_min}} \end{cases}. \quad (16b)$$

VPD, Δ , and γ in Eqs. (8) and (11) were estimated with the same methods used in Eq. (1), whereas the terms describing the available energy of the soil and vegetation components, A_s and A_c , were estimated using the fractional vegetation cover f_c (Mu et al. 2007; Zhang et al. 2009). The fractional vegetation cover f_c was deduced from the measured LAI according to Walthall et al. (2004). The determination of the empirical coefficients (e.g., b) and biophysical values (e.g., c_L and $T_{\text{min_open}}/T_{\text{min_close}}$) required in the $r_{s,c}$ parameterization [Eqs. (13)–(16)] is described in section 2c(3).

3) CALIBRATION METHOD USED IN RESISTANCE PARAMETERIZATIONS

The empirical coefficients and biophysical values required in resistance (i.e., r_s and $r_{s,c}$) estimation were determined using two methods. First, we used prior knowledge (precalibrated values) from the literature as measurements of biophysical values are scarce, especially in data-poor arid northwest China, due to a lack of observations. For the one-source PM equations, values from an experimental site consisting of maize adjacent to our study area in Li et al. (2015) were used (Table 1). For the two-source PM_Mu and PM_PLSH, values were cited from Mu et al. (2007) and Zhang et al. (2009), respectively (Table 1). Second, we calibrated the empirical and biophysical values through a nonlinear least squares method [Eq. (17)], which is a nonlinear regression approach widely applied for constrained problems:

$$\begin{aligned} \min_{\theta} \sum_{i=1}^n (M_i - O_i)^2 &= \min_{\theta} \|f(\theta, x) - O\|_2^2 \\ &= \min_{\theta} \sum_{i=1}^n [f(\theta, x_i) - O_i]^2, \end{aligned} \quad (17)$$

where O_i and M_i are paired LE observations and model estimates, respectively; $f(\theta, x)$ is the nonlinear objective function and defined as the PM equations in the above

sections, where θ are parameters to be calibrated in the PM equation; x represents the remaining variables; and n is the number of datasets.

Calibration was performed for the maize sites because data were limited for the orchard and vegetable areas, with fewer than 200 observations each, as only one EC system was installed in each. During the calibration, the entire dataset was disrupted randomly and divided into calibration and validation groups with fixed proportions. For example, if half of the available datasets were classified into the calibration group, the remaining data belonging to the validation group were used for independent validation. To obtain the best optimization, we performed nine tests for each calibration by selecting a calibration group with a ratio ranging from 10% to 90% (with an increment of 10% for each test). The trust-region-reflective algorithm, based on the interior-reflective Newton method, was used to solve the nonlinear least squares Eq. (17) in MATLAB (MathWorks Inc., United States).

3. Results

a. Differences among the LE estimates

The LE values estimated from the one- and two-source PM equations with the default resistance methods listed in section 2b exhibited significant differences for a given land type in most cases (Fig. 4). Generally, the mean absolute percent error (MAPE) was greater than 32% for the PM equations, and the one-source PM equation performed slightly better than the two-source PM equation (Fig. 5). The one-source PM_JA method (with an MAPE of 31.7%) displayed the smallest errors in the LE estimates, whereas the empirical PM_KP approach (with an MAPE of 35.5%) led to the largest uncertainty. For the two-source method, the MAPE values were 41.5% and 52.7% for PM_Mu and PM_PLSH, respectively.

FIG. 4. Box-and-whisker plots showing the latent heat flux (LE) values of different land types in the 2012 growing season. Note that EC represents observational data, and the other four labels are estimates based on the default PM methods using uncalibrated parameters; the legends of the figures are similar to those for Fig. 3b, and an asterisk indicates that the estimates are significantly different from the corresponding observations (ANOVA, $p < 0.05$).

b. Sources of uncertainty in the LE estimates

Notably, the differences in the LE estimates and model performances between the one-source and two-source PM equations were caused by the different resistance parameterizations. Specifically, the difference for the one-source model was between the resistance parameterizations [Eqs. (3) and (5)], whereas the difference was caused by Eqs. (13) and (15) for the two-source model. Nonetheless, it should be noted that the LE values measured from the EC towers may have uncertainties varying from 1% to 16% (Xu et al. 2013; Wang et al. 2015); as is the usual practice in the research community (e.g., Zhang et al. 2010; Ershadi et al. 2015; Mallick et al. 2015), we treated the measurements as true and did not include the observational uncertainty in the following analyses.

1) UNCERTAINTY IN DETERMINING THE BIOPHYSICAL PARAMETERS

When parameterizing resistances, different biophysical parameters (shown in Table 1) are required both in the Jarvis–Stewart framework and in other physical methods (Franks et al. 2017). However, these biophysical parameters likely depend on the species and life cycles of different plants. Although leaf-level values can be measured, the representativeness of those measurements is questionable, and measurements for plant species under different water and climatic combinations are scarce. As such, uncertainties in ET estimation are likely to be generated when biophysical boundaries are required for parameterizing resistances, especially in

areas without (or with limited) observations and a priori knowledge.

Taking the one-source PM_JA equation as an example, measurements of the minimum stomatal resistance r_{smin} require optimal conditions, which are difficult to find (or determine). For example, when estimating the canopy resistance of maize at an experimental station in northwest China, the optimal r_{smin} was 20 s m^{-1} based on observations and simulations between 2007 and 2008 (S. Li et al. 2013), but the optimal value was found to be 150 s m^{-1} in another study by the same research group (Li et al. 2016). In this study, the default r_{smin} was set to 20 s m^{-1} ; if the value had been set to 150 s m^{-1} , obvious differences would have been generated in the LE estimation (Fig. 6a). These results and others (e.g., Riveros-Burgos 2019) indicate that if some key biophysical variables (e.g., r_{smin}) are not properly determined (i.e., deduced from site experiments rather than from an understanding of the mechanistic theory), significant errors will be generated in the ET estimation, even when applied to other sites with similar environmental conditions, as shown here.

Similar problems are encountered when attempting to obtain the lower, optimal, and upper air temperature limits (or VPD limits) of stomatal activity shown in Table 1. Certain values are typically assumed for each plant functional type because these parameters for each species can vary temporally because of plant acclimation (Kumarathunge et al. 2019). For example, Hatfield et al. (2011) summarized the optimal temperatures for several crops with values ranging from 26°C (wheat) to 37°C (cotton). In an ET model called ETmonitor, the lower, optimal, and upper air temperatures for C4 plants, such as maize, were set to 5° , 35° , and 55°C , respectively (Hu and Jia 2015). S. Li et al. (2013) suggested that the optimal temperature is 10°C for maize. Hence, if the optimal temperature is changed from the default value of 35° to 10°C , r_s increases, producing lower LE values with a mean difference of 208 W m^{-2} (Fig. 6b).

2) DIFFERENCES AMONG THE RESISTANCE PARAMETERIZATIONS

Figure 7a shows the considerable differences between r_{s_JA} , which was estimated in accordance with Eq. (3), and r_{s_KP} , which was estimated in accordance with Eq. (5). The average difference between the r_{s_JA} and r_{s_KP} estimates was 267 s m^{-1} if values $> 1000 \text{ s m}^{-1}$ were assumed to be outliers, which led to substantial differences in the LE estimates. Similarly, obvious differences were noted between $r_{s_c_Mu}$, which was estimated in accordance with Eqs. (12) and (13), and $r_{s_c_PLSH}$, which was estimated in accordance with Eqs. (12) and (15) (Fig. 7b). Notably, several algorithms

FIG. 5. Comparison between the estimated and measured daytime (0700–1900 UTC + 8) latent heat flux (LE) values at vegetated sites. Note that EC represents eddy covariance observations, while the other four labels are estimates based on the default PM methods using uncalibrated parameters; MAE and MAPE represent the mean absolute error and mean absolute percent error, respectively. The temporal scale of the data is 30 min.

can be used for a given stress function in the Jarvis-Stewart framework (Table 2). For example, we used a linear algorithm to parameterize $f(\text{VPD})$ in the PM_JA model; however, the relationship between $f(\text{VPD})$ and VPD can be exponential (S. Li et al. 2013; Li et al. 2015). Nevertheless, the results in Fig. 7c suggest that changing the parameterization of $f(\text{VPD})$ from linear to an exponential algorithm can cause overestimation of LE. Thus, the method for estimating resistances and their parameterizations can be major sources of uncertainty in the estimation of ET.

3) COMPLEXITY OF RESISTANCE ALGORITHMS

The results from the one-source PM_JA method were more similar to the observations with respect to MAPE

than the LE_KP values, which were estimated using the surface resistance parameterizations from the empirical PM_KP method. However, the relatively complex two-source PM equation performed more poorly than the one-source PM equation, as shown in section 3a, which was likely because the two-source PM equation requires more complex parameterizations. Nonetheless, the performance of PM_Mu was 10% better than that of PM_PLSh in terms of the MAPE (Fig. 5) because even though the only difference between these algorithms was the canopy resistance parameterization, the former requires fewer biophysical parameters than the latter and therefore avoids generating uncertainty. We performed a sensitivity test by adding a perturbation (with an increment of 10%) to each input variable

FIG. 6. Differences in the latent heat flux (LE) estimates from modifications to the r_s calculation in PM_JA: (a) modifying $r_{s\min}$, (b) modifying the optimal temperature, and (c) modifying the parameterization of $f(\text{VPD})$. Note that the LE values were estimated using PM_JA; MAE represents the mean absolute error; LE_JA_20 and LE_JA_150 represent the estimated LE values when setting the minimum stomatal resistance $r_{s\min}$ to 20 and 150 s m^{-1} , respectively; LE_JA_10 and LE_JA_35 represent the estimated LE values when parameterizing $f(T_o)$ using optimal temperatures of 10° and 35°C, respectively; and LE_JA_L and LE_JA_Exp represent the estimated LE values when parameterizing $f(\text{VPD})$ using linear and exponential algorithms, respectively [the values were derived from the literature; see section 3b(1) for details].

in the r_s parameterization and found that the most important variables influencing r_s were the VPD and air temperature, with average MAPE values at least 9 times larger than those of the other variables. We also found that in the Jarvis–Stewart framework, more uncertainty was generated in more complex algorithms than in simple ones (Fig. 8).

4. Discussion

a. Reducing uncertainties in resistance parameterizations

To reduce the uncertainties, we calibrated the model parameters. The results in Table 1 show the differences between the calibrated and default values. The performance of the one-source PM equation improved remarkably after calibration (Fig. 9) with MAPE values of 16.3% and 12.5% for LE_JA and LE_KP, respectively. Considerable improvement was also observed for the two-source PM_PLSH, as evidenced by a decrease in the MAPE of 14%, whereas only marginal improvement (i.e., a MAPE decrease of <4%) was observed for the two-source PM_Mu equation. The results indicate that the PM equation can only be used when the exact values of the resistances are known and that the calibrated two-source PM equation does not extrapolate well, as summarized in Blöschl et al. (2019). This can explain why an analytical solution of the canopy-substrate resistance, rather than a calibration-based approach, was used for estimating ET in the PM equation (Mallick et al. 2014, 2015, 2016, 2018a,b; Bhattarai et al. 2018).

The calibration was performed by trial and error and requires additional observation datasets, which are difficult to obtain in most applications. In this

study, we were able to calibrate the biophysical parameters only for maize due to the limited data for the orchard and vegetable fields (with <200 observations). Even if data are available to perform the calibration, such calibrated biophysical values are not transferable across different time scales (even for a biome under similar environmental conditions), as shown here and in other studies (e.g., H. Wang et al. 2016). In fact, the uncertainty caused by model structure and model calibration is an unsolved problem in ET-related hydrological studies (Blöschl et al. 2019). Moreover, dividing the data into calibration and validation groups is a subjective procedure that affects both the numerical values of the calibrated parameters and the validation results. In another test, we increased the number of calibration datasets; however, we found that the performance of the PM equation exhibited only a marginal change (Fig. 10). These results indicate that performing additional parameterizations, increasing algorithmic complexity, and calibrating more parameters enhance the uncertainty and errors.

b. Reducing uncertainties by avoiding resistance parameterizations

Avoiding the use of resistances may be a solution to reduce the uncertainties in the estimation of ET. Several methods that eliminate resistances have been proposed and provide comparable accuracy; examples include the three-temperature (3T) model (Qiu et al. 2006; Xiong et al. 2015; Y. Q. Wang et al. 2016), the surface temperature initiated closure model (Mallick et al. 2014, 2015; Bhattarai et al. 2018, 2019), the Priestley–Taylor method (Priestley and Taylor 1972; García et al. 2013;

FIG. 7. Differences in surface resistance between the (a) one- and (b) two-source PM schemes. Note that r_{s_JA} and r_{s_KP} are r_s values from the default Jarvis–Stewart framework using uncalibrated parameters, r_{s_PM} is the inverse of the one-source PM equation, and r_{s,c_Mu} and r_{s,c_PLSH} are the values from the default PM_Mu and PM_PLSH algorithms using uncalibrated parameters, respectively.

Ai and Yang 2016), the triangle or trapezoidal method (Price 1990; Long and Singh 2012), the maximum entropy production model (Wang and Bras 2011; Hajji et al. 2018), the complementary relationship model (Bouchet 1963; Brutsaert 2015; Ma et al. 2019), the nonparametric approach (Liu et al. 2012), and the surface renewal method (Paw U et al. 1995).

Figure 11 shows that the LEs estimated at the 16 vegetated flux sites from the 3T model (see the supplemental material for a detailed model description), which does not explicitly include any resistance parameterizations, were generally close to the observed values, with an MAPE of 19%. The 3T model requires net radiation, soil heat flux, air temperature, and soil and

TABLE 2. Different algorithms that represent the environmental forces for leaf resistance in the PM_JA model.

Linear algorithm	Exponential algorithm
$f(R_s) = R_s(1000 + k_1)/1000(R_s + k_1)$ (S. Li et al. 2013; Li et al. 2015) $f(T_a) = (T_a - T_L)(T_H - T_a)^t / [(T_{op} - T_L)(T_H - T_{op})^t]$ (Stewart 1988), where $t = (T_H - T_{op}) / (T_{op} - T_L)$ (Hu and Jia 2015) $f(VPD) = 1 - k_2 VPD$ (Mo et al. 2004; Hu and Jia 2015)	$f(R_s) = 1 - \exp(R_s/500)$ (Mo et al. 2004; Hu and Jia 2015) $f(T_a) = (T_a - T_L)(T_H - T_a)^t / [(T_{op} - T_L)(T_H - T_{op})^t]$ (Stewart 1988), where $t = (T_H \times T_{op}) / (T_{op} - T_L)$ (S. Li et al. 2013; Li et al. 2015) $f(VPD) = \exp(-k_2 VPD)$ (S. Li et al. 2013; Li et al. 2015)

FIG. 8. Sensitivity analysis for (a)–(d) surface resistance and (e)–(h) latent heat flux (LE) estimates by adding an incremental perturbation to each input variable when parameterizing r_s (or $r_{s,c}$). Note that perturbation was set to 10%, 20%, 30%, 40%, 50%, 60%, 70%, 80%, and 90% of standard deviation. MAPE represents the mean absolute percent error between estimates with and without perturbation; MAPE values $> 100\%$ are not shown.

canopy temperatures as inputs, and the use of fewer model inputs leads to a decreased dependence on observational data; hence, the number of LE estimates from the 3T model was greater than those from the one- and two-source PM equations shown in Fig. 5. Moreover, the performance of the 3T model was comparable to the performances of the calibrated PM equations in Fig. 9; this finding indicates that by eliminating resistance parameterizations, uncertainties generated by such processes can be avoided.

5. Conclusions

This study investigated the uncertainties in the estimation of ET generated by resistance terms by comparing different resistance parameterizations under one- and two-source PM methods. The MAPE varied from 32% to 53% for the one- and two-source PM equations with different resistance parameterizations. If the parameters were calibrated properly prior to the resistance estimation, the performance of the one-source PM equation improved

FIG. 9. Performances of the PM equations after calibrating the biophysical parameters prior to the resistance parameterization for the maize sites. Note that MAE and MAPE represent the mean absolute error and mean absolute percent error, respectively, and the temporal scale of the data is 30 min (the same as in Fig. 5).

considerably (with MAPE values from 12% to 16%), whereas the MAPEs for the two-source PM equation were 38%. Therefore, increasing the number of resistances

increases the corresponding error, and the calibrated two-source PM equation requiring overly complicated parameterizations does not extrapolate well. We conclude the

FIG. 10. Change trends of the one- and two-source PM equation performances with an increase in the ratio of the number of calibration datasets to the total number of datasets. Note that the error bar represents the standard deviation for the estimates from data randomly sampled to perform calibration 100 times at a given ratio.

FIG. 11. An example showing the performance of the three-temperature (3T) model, which does not explicitly include any resistance parameterizations. The temporal scale of the data is 30 min (the same as in Fig. 5).

following: 1) different resistance parameterizations in the PM equation can produce substantial uncertainties; 2) the empirical and biophysical values required in resistance parameterizations are responsible for uncertainty, and care should thus be taken when using prior knowledge as an alternative because the values are not transferable across temporal scales and between areas; 3) increasingly complex resistance parameterizations lead to larger uncertainties in the estimation of ET, and the large number of ambiguous parameterizations of the resistances and related uncertainties challenge the current status quo of using such formulations in the PM equation; and 4) models without resistance parameterizations exhibit reduced uncertainties in ET estimates.

Acknowledgments. We gratefully acknowledge the financial support from the National Natural Science Foundation of China (41671416) and the China Scholarship Council (201806010242, 201606380186). We also thank the Heihe Watershed Applied Telemetry Experimental Research (HiWATER) project for their support with the EC observation data. We are also grateful to the reviewers for their insightful and constructive comments.

APPENDIX

Variables and Abbreviations

Variables and abbreviations are listed in Table A1.

TABLE A1. Summary and description of the variables.

Variable	Unit	Description
ET	mm	Evapotranspiration (evaporation + transpiration) as depth of water
E_c	mm	Vegetation transpiration
E_s	mm	Soil evaporation
L	J kg^{-1}	Latent heat of vaporization
$L(\text{ET})$	W m^{-2}	Evapotranspiration (evaporation + transpiration) as latent heat flux
LE_c	W m^{-2}	Vegetation transpiration as latent heat flux
LE_s	W m^{-2}	Soil evaporation as latent heat flux
R_n	W m^{-2}	Net radiation
$R_{n,s}$	W m^{-2}	Net radiation of the soil component
$R_{n,c}$	W m^{-2}	Net radiation of the vegetation component
R_s	W m^{-2}	Solar radiation
G	W m^{-2}	Soil heat flux
H	W m^{-2}	Sensible heat flux
A	W m^{-2}	Available energy for ET: $R_n - G$
T_a	$^{\circ}\text{C}$	Air temperature
T_{0s}	$^{\circ}\text{C}$	Soil surface temperature
T_{0c}	$^{\circ}\text{C}$	Canopy temperature
T_L	$^{\circ}\text{C}$	Lower air temperature limits of stomatal activity method
T_{op}	$^{\circ}\text{C}$	Optimal air temperature limits of stomatal activity method
T_H	$^{\circ}\text{C}$	Upper air temperature limits of stomatal activity method
r_a	m s^{-1}	Aerodynamic resistance
$r_{a,c}$	m s^{-1}	Aerodynamic resistance for canopy
$r_{a,s}$	m s^{-1}	Aerodynamic resistance for soil surface
r_s	m s^{-1}	Surface resistance
r_{smin}	m s^{-1}	Minimum stomatal resistance under optimal conditions
$r_{s,c}$	m s^{-1}	Canopy resistance
$r_{s,s}$	m s^{-1}	Soil surface resistance
r_{sc}	m s^{-1}	Resistance to convective heat transfer
r_{ss}	m s^{-1}	Resistance to radiative heat transfer
g_s	m s^{-1}	Leaf stomatal (surface) conductance
g_c	m s^{-1}	Canopy conductance
gl_{sh}	m s^{-1}	Leaf conductance to H per unit LAI
Δ	—	Slope of the saturation vapor pressure with respect to temperature
γ	$\text{kPa } ^{\circ}\text{C}^{-1}$	Psychrometric constant
R_h	—	Relative humidity
VPD	kPa	Vapor pressure deficit
ρ_a	kg m^{-3}	Mean air density at constant pressure
C_p	$\text{J kg}^{-1} ^{\circ}\text{C}^{-1}$	Specific heat capacity of air
z_r	m	Reference height
z_{0m}	m	Surface roughness length for momentum
z_{0h}	m	Surface roughness length for heat
u_{zx}	m s^{-1}	Wind speed at reference height
D	m	Displacement height
θ	$\text{cm}^3 \text{cm}^{-3}$	Soil water
θ_w	$\text{cm}^3 \text{cm}^{-3}$	Wilting point
θ_f	$\text{cm}^3 \text{cm}^{-3}$	Field capacity

REFERENCES

- Ai, Z., and Y. Yang, 2016: Modification and validation of Priestley–Taylor model for estimating cotton evapotranspiration under plastic mulch condition. *J. Hydrometeor.*, **17**, 1281–1293, <https://doi.org/10.1175/JHM-D-15-0151.1>.
- Allen, R. G., L. S. Pereira, D. Raes, and M. Smith, 1998: Crop evapotranspiration: Guidelines for computing crop water requirements. FAO Irrigation and Drainage Paper 56, 300 pp., <http://www.fao.org/3/X0490E/X0490E00.htm>.
- Bai, Y., X. Y. Li, S. M. Liu, and P. Wang, 2017: Modelling diurnal and seasonal hysteresis phenomena of canopy conductance in an oasis forest ecosystem. *Agric. For. Meteorol.*, **246**, 98–110, <https://doi.org/10.1016/j.agrformet.2017.06.006>.
- , and Coauthors, 2019: Quantifying plant transpiration and canopy conductance using eddy flux data: An underlying water use efficiency method. *Agric. For. Meteorol.*, **271**, 375–384, <https://doi.org/10.1016/j.agrformet.2019.02.035>.
- Baldocchi, D. D., R. J. Luxmoore, and J. L. Hatfield, 1991: Discerning the forest from the trees: An essay on scaling canopy stomatal conductance. *Agric. For. Meteorol.*, **54**, 197–226, [https://doi.org/10.1016/0168-1923\(91\)90006-C](https://doi.org/10.1016/0168-1923(91)90006-C).
- Ball, J. T., I. E. Woodrow, and J. A. Berry, 1987: A model predicting stomatal conductance and its contribution to control of photosynthesis under different environmental conditions. *Progress in Photosynthesis Research*, Vol. 4, J. Biggins, Ed., Springer, 221–224, https://doi.org/10.1007/978-94-017-0519-6_48.
- Barr, A. G., K. Morgenstern, T. A. Black, J. H. McCaughey, and Z. Nesic, 2006: Surface energy balance closure by the eddy-covariance method above three boreal forest stands and implications for the measurement of the CO₂ flux. *Agric. For. Meteorol.*, **140**, 322–337, <https://doi.org/10.1016/j.agrformet.2006.08.007>.
- Bhattarai, N., K. Mallick, N. A. Brunsell, G. Sun, and M. Jain, 2018: Regional evapotranspiration from an image-based implementation of the Surface Temperature Initiated Closure (STIC1. 2) model and its validation across an aridity gradient in the conterminous US. *Hydrol. Earth Syst. Sci.*, **22**, 2311–2341, <https://doi.org/10.5194/hess-22-2311-2018>.
- , —, J. Stuart, B. D. Vishwakarma, R. Niraula, S. Sen, and M. Jain, 2019: An automated multi-model evapotranspiration mapping framework using remotely sensed and reanalysis data. *Remote Sens. Environ.*, **229**, 69–92, <https://doi.org/10.1016/j.rse.2019.04.026>.
- Blöschl, G., and Coauthors, 2019: Twenty-three unsolved problems in hydrology (UPH)—A community perspective. *Hydrol. Sci. J.*, **64**, 1141–1158, <https://doi.org/10.1080/02626667.2019.1620507>.
- Bouchet, R. J., 1963: Evapotranspiration réelle, évapotranspiration potentielle, et production agricole. *Ann. Agron.*, **14**, 743–824.
- Boulet, G., and Coauthors, 2015: The SPARSE model for the prediction of water stress and evapotranspiration components from thermal infra-red data and its evaluation over irrigated and rainfed wheat. *Hydrol. Earth Syst. Sci.*, **19**, 4653–4672, <https://doi.org/10.5194/hess-19-4653-2015>.
- Brutsaert, W., 2015: A generalized complementary principle with physical constraints for land-surface evaporation. *Water Resour. Res.*, **51**, 8087–8093, <https://doi.org/10.1002/2015WR017720>.
- , and H. Stricker, 1979: An advection-aridity approach to estimate actual regional evapotranspiration. *Water Resour. Res.*, **15**, 443–450, <https://doi.org/10.1029/WR015i002p00443>.
- Buckley, T. N., 2017: Modeling stomatal conductance. *Plant Physiol.*, **174**, 572–582, <https://doi.org/10.1104/pp.16.01772>.
- Damour, G., T. Simonneau, H. Cochard, and L. Urban, 2010: An overview of models of stomatal conductance at the leaf level. *Plant Cell Environ.*, **33**, 1419–1438, <https://doi.org/10.1111/j.1365-3040.2010.02181.x>.
- Deng, Z., H. Guan, J. Hutson, M. A. Forster, Y. Wang, and C. T. Simmons, 2017: A vegetation-focused soil-plant-atmospheric continuum model to study hydrodynamic soil-plant water relations. *Water Resour. Res.*, **53**, 4965–4983, <https://doi.org/10.1002/2017WR020467>.
- Ershadi, A., M. F. McCabe, J. P. Evans, and E. F. Wood, 2015: Impact of model structure and parameterization on Penman–Monteith type evaporation models. *J. Hydrol.*, **525**, 521–535, <https://doi.org/10.1016/j.jhydrol.2015.04.008>.
- Franks, P. J., J. A. Berry, D. L. Lombardozzi, and G. B. Bonan, 2017: Stomatal function across temporal and spatial scales: Deep-time trends, land-atmosphere coupling and global models. *Plant Physiol.*, **174**, 583–602, <https://doi.org/10.1104/pp.17.00287>.
- , G. B. Bonan, J. A. Berry, D. L. Lombardozzi, N. M. Holbrook, N. Herold, and K. W. Oleson, 2018: Comparing optimal and empirical stomatal conductance models for application in Earth system models. *Global Change Biol.*, **24**, 5708–5723, <https://doi.org/10.1111/gcb.14445>.
- García, M., and Coauthors, 2013: Actual evapotranspiration in drylands derived from in-situ and satellite data: Assessing biophysical constraints. *Remote Sens. Environ.*, **131**, 103–118, <https://doi.org/10.1016/j.rse.2012.12.016>.
- Gerhards, M., M. Schlerf, K. Mallick, and T. Udelhoven, 2019: Challenges and future perspectives of multi-/hyperspectral thermal infrared remote sensing for crop water-stress detection: A review. *Remote Sens.*, **11**, 1240, <https://doi.org/10.3390/rs11101240>.
- Hajji, I., D. F. Nadeau, B. Music, F. Ancil, and J. Wang, 2018: Application of the maximum entropy production model of evapotranspiration over partially vegetated water-limited land surfaces. *J. Hydrometeorol.*, **19**, 989–1005, <https://doi.org/10.1175/JHM-D-17-0133.1>.
- Hatfield, J. L., K. J. Boote, B. A. Kimball, L. H. Ziska, R. C. Izaurralde, D. Ort, A. M. Thomson, and D. W. Wolfe, 2011: Climate impacts on agriculture: Implications for crop production. *Agron. J.*, **103**, 351–370, <https://doi.org/10.2134/agronj2010.0303>.
- Hu, G., and L. Jia, 2015: Monitoring of evapotranspiration in a semi-arid inland river basin by combining microwave and optical remote sensing observations. *Remote Sens.*, **7**, 3056–3087, <https://doi.org/10.3390/rs70303056>.
- Huang, Y., M. S. Salama, Z. Su, R. van der Velde, D. Zheng, M. S. Krol, A. Y. Hoekstra, and Y. Zhou, 2016: Effects of roughness length parameterizations on regional scale land surface modelling of alpine grasslands in the Yangtze River basin. *J. Hydrometeorol.*, **17**, 1069–1085, <https://doi.org/10.1175/JHM-D-15-0049.1>.
- Irmak, S., D. Mutiibwa, A. Irmak, T. J. Arkebauer, A. Weiss, D. L. Martin, and D. E. Eisenhauer, 2008: On the scaling up leaf stomatal resistance to canopy resistance using photosynthetic photon flux density. *Agric. For. Meteorol.*, **148**, 1034–1044, <https://doi.org/10.1016/j.agrformet.2008.02.001>.
- Jarvis, P. G., 1976: The interpretation of the variations in leaf water potential and stomatal conductance found in canopies in the field. *Philos. Trans. Roy. Soc. London*, **B273**, 593–610, <https://doi.org/10.1098/RSTB.1976.0035>.
- Jefferson, J. L., R. M. Maxwell, and P. G. Constantine, 2017: Exploring the sensitivity of photosynthesis and stomatal resistance parameters in a land surface model. *J. Hydrometeorol.*, **18**, 897–915, <https://doi.org/10.1175/JHM-D-16-0053.1>.

- Katerji, N., and A. Perrier, 1983: Modélisation de l'évapotranspiration réelle ETR d'une parcelle de luzerne: Rôle d'un coefficient cultural. *Agronomie*, **3**, 513–521, <https://doi.org/10.1051/agro:19830603>.
- Kumarathunge, D. P., and Coauthors, 2019: Acclimation and adaptation components of the temperature dependence of plant photosynthesis at the global scale. *New Phytol.*, **222**, 768–784, <https://doi.org/10.1111/nph.15668>.
- Leuning, R., F. M. Kelliher, D. G. G. de Prury, and E.-D. Schulze, 1995: Leaf nitrogen, photosynthesis, conductance and transpiration: Scaling from leaves to canopy. *Plant Cell Environ.*, **18**, 1183–1200, <https://doi.org/10.1111/j.1365-3040.1995.tb00628.x>.
- Li, S., and Coauthors, 2013: Quantifying the combined effects of climatic, crop and soil factors on surface resistance in a maize field. *J. Hydrol.*, **489**, 124–134, <https://doi.org/10.1016/j.jhydrol.2013.03.002>.
- , L. Zhang, S. Kang, L. Tong, T. Du, X. Hao, and P. Zhao, 2015: Comparison of several surface resistance models for estimating crop evapotranspiration over the entire growing season in arid regions. *Agric. For. Meteorol.*, **208**, 1–15, <https://doi.org/10.1016/j.agrformet.2015.04.002>.
- Li, X., and Coauthors, 2013: Heihe Watershed Allied Telemetry Experimental Research (HiWATER): Scientific objectives and experimental design. *Bull. Amer. Meteor. Soc.*, **94**, 1145–1160, <https://doi.org/10.1175/BAMS-D-12-00154.1>.
- , S. Kang, F. Li, X. Jiang, L. Tong, R. Ding, S. Li, and T. Du, 2016: Applying segmented Jarvis canopy resistance into Penman-Monteith model improves the accuracy of estimated evapotranspiration in maize for seed production with film-mulching in arid area. *Agric. Water Manage.*, **178**, 314–324, <https://doi.org/10.1016/j.agwat.2016.09.016>.
- , P. Gentile, C. Lin, S. Zhou, Z. Sun, Y. Zheng, J. Liu, and C. Zheng, 2019: A simple and objective method to partition evapotranspiration into transpiration and evaporation at eddy-covariance sites. *Agric. For. Meteorol.*, **265**, 171–182, <https://doi.org/10.1016/j.agrformet.2018.11.017>.
- Li, Y., and Coauthors, 2019: Evaluating soil resistance formulations in thermal-based two-source energy balance (TSEB) model: Implications for heterogeneous semiarid and arid regions. *Water Resour. Res.*, **55**, 1059–1078, <https://doi.org/10.1029/2018WR022981>.
- Liu, S. M., L. Lu, D. Mao, and L. Jia, 2007: Evaluating parameterizations of aerodynamic resistance to heat transfer using field measurements. *Hydrol. Earth Syst. Sci.*, **11**, 769–783, <https://doi.org/10.5194/hess-11-769-2007>.
- , Z. W. Xu, W. Z. Wang, J. Bai, Z. Jia, M. Zhu, and J. M. Wang, 2011: A comparison of eddy-covariance and large aperture scintillometer measurements with respect to the energy balance closure problem. *Hydrol. Earth Syst. Sci.*, **15**, 1291–1306, <https://doi.org/10.5194/hess-15-1291-2011>.
- , and Coauthors, 2016: Upscaling evapotranspiration measurements from multi-site to the satellite pixel scale over heterogeneous land surfaces. *Agric. For. Meteorol.*, **230–231**, 97–113, <https://doi.org/10.1016/j.agrformet.2016.04.008>.
- , and Coauthors, 2018: The Heihe integrated observatory network: A basin-scale land surface processes observatory in China. *Vadose Zone J.*, **17**, 180072, <https://doi.org/10.2136/vzj2018.04.0072>.
- Liu, Y. B., T. Hiyama, T. Yasunari, and H. Tanaka, 2012: A non-parametric approach to estimating terrestrial evaporation: Validation in eddy covariance sites. *Agric. For. Meteorol.*, **157**, 49–59, <https://doi.org/10.1016/j.agrformet.2012.01.012>.
- Long, D., and V. P. Singh, 2012: A Two-source Trapezoid Model for Evapotranspiration (TTME) from satellite imagery. *Remote Sens. Environ.*, **121**, 370–388, <https://doi.org/10.1016/j.rse.2012.02.015>.
- , L. Longuevergne, and B. R. Scanlon, 2014: Uncertainty in evapotranspiration from land surface modeling, remote sensing, and GRACE satellites. *Water Resour. Res.*, **50**, 1131–1151, <https://doi.org/10.1002/2013WR014581>.
- Ma, N., J. Szilagyi, Y. Zhang, and W. Liu, 2019: Complementary-relationship-based modeling of terrestrial evapotranspiration across China during 1982–2012: Validations and spatiotemporal analyses. *J. Geophys. Res. Atmos.*, **124**, 4326–4351, <https://doi.org/10.1029/2018JD029850>.
- Mallick, K., and Coauthors, 2014: A Surface Temperature Initiated Closure (STIC) for surface energy balance fluxes. *Remote Sens. Environ.*, **141**, 243–261, <https://doi.org/10.1016/j.rse.2013.10.022>.
- , and Coauthors, 2015: Reintroducing radiometric surface temperature into the Penman-Monteith formulation. *Water Resour. Res.*, **51**, 6214–6243, <https://doi.org/10.1002/2014WR016106>.
- , and Coauthors, 2016: Canopy-scale biophysical controls of transpiration and evaporation in the Amazon Basin. *Hydrol. Earth Syst. Sci.*, **20**, 4237–4264, <https://doi.org/10.5194/hess-20-4237-2016>.
- , and Coauthors, 2018a: Bridging thermal infrared sensing and physically-based evapotranspiration modeling: From theoretical implementation to validation across an aridity gradient in Australian ecosystems. *Water Resour. Res.*, **54**, 3409–3435, <https://doi.org/10.1029/2017WR021357>.
- , L. Wandera, N. Bhattarai, R. Hostache, M. Kleniewska, and J. Chormanski, 2018b: A critical evaluation on the role of aerodynamic and canopy-surface conductance parameterization in SEB and SVAT models for simulating evapotranspiration: A case study in the upper Biebrza National Park wetland in Poland. *Water*, **10**, 1753, <https://doi.org/10.3390/w10121753>.
- Matheny, A. M., and Coauthors, 2014: Characterizing the diurnal patterns of errors in the prediction of evapotranspiration by several land-surface models: An NACP analysis. *J. Geophys. Res. Biogeosci.*, **119**, 1458–1473, <https://doi.org/10.1002/2014JG002623>.
- Medlyn, B. E., and Coauthors, 2011: Reconciling the optimal and empirical approaches to modelling stomatal conductance. *Global Change Biol.*, **17**, 2134–2144, <https://doi.org/10.1111/j.1365-2486.2010.02375.x>.
- Mo, X., S. Liu, Z. Lin, and Z. Zhao, 2004: Simulating temporal and spatial variation of evapotranspiration over the Lushi basin. *J. Hydrol.*, **285**, 125–142, <https://doi.org/10.1016/j.jhydrol.2003.08.013>.
- Monteith, J. L., 1965: Evaporation and environment. *Symp. Soc. Exp. Biol.*, **19**, 205–234.
- Morillas, L., R. Leuning, L. Villagarcía, M. García, P. Serrano-Ortiz, and F. Domingo, 2013: Improving evapotranspiration estimates in Mediterranean drylands: The role of soil evaporation. *Water Resour. Res.*, **49**, 6572–6586, <https://doi.org/10.1002/wrcr.20468>.
- Mu, Q., F. A. Heinsch, M. Zhao, and S. W. Running, 2007: Development of a global evapotranspiration algorithm based on MODIS and global meteorology data. *Remote Sens. Environ.*, **111**, 519–536, <https://doi.org/10.1016/j.rse.2007.04.015>.
- Norman, J. M., W. P. Kustas, and K. S. Humes, 1995: Source approach for estimating soil and vegetation energy fluxes in observations of directional radiometric surface temperature. *Agric. For. Meteorol.*, **77**, 263–293, [https://doi.org/10.1016/0168-1923\(95\)02265-Y](https://doi.org/10.1016/0168-1923(95)02265-Y).
- Paw U, K. T., J. Qiu, H.-B. Su, T. Watanabe, and Y. Brunet, 1995: Surface renewal analysis: A new method to obtain scalar fluxes without velocity data. *Agric. For. Meteorol.*, **74**, 119–137, [https://doi.org/10.1016/0168-1923\(94\)02182-J](https://doi.org/10.1016/0168-1923(94)02182-J).

- Price, J. C., 1990: Using spatial context in satellite data to infer regional scale evapotranspiration. *IEEE Trans. Geosci. Remote Sens.*, **28**, 940–948, <https://doi.org/10.1109/36.58983>.
- Priestley, C. H. B., and R. J. Taylor, 1972: On the assessment of surface heat flux and evaporation using large-scale parameters. *Mon. Wea. Rev.*, **100**, 81–92, [https://doi.org/10.1175/1520-0493\(1972\)100<0081:OTAOSH>2.3.CO;2](https://doi.org/10.1175/1520-0493(1972)100<0081:OTAOSH>2.3.CO;2).
- Qiu, G. Y., P. J. Shi, and L. M. Wang, 2006: Theoretical analysis of a remotely measurable soil evaporation transfer coefficient. *Remote Sens. Environ.*, **101**, 390–398, <https://doi.org/10.1016/j.rse.2006.01.007>.
- Qu, Y. H., Y. Q. Zhu, W. C. Han, J. D. Wang, and M. G. Ma, 2014: Crop leaf area index observations with a wireless sensor network and its potential for validating remote sensing products. *IEEE J. Sel. Top. Appl. Earth Obs. Remote Sens.*, **7**, 431–444, <https://doi.org/10.1109/JSTARS.2013.2289931>.
- Rana, G., and N. Katerji, 1998: A measurement based sensitivity analysis of Penman-Monteith actual evapotranspiration model for crops of different height and in contrasting water status. *Theor. Appl. Climatol.*, **60**, 141–149, <https://doi.org/10.1007/s007040050039>.
- Rigden, A., D. Li, and G. Salvucci, 2018: Dependence of thermal roughness length on friction velocity across land cover types: A synthesis analysis using AmeriFlux data. *Agric. For. Meteorol.*, **249**, 512–519, <https://doi.org/10.1016/j.agrformet.2017.06.003>.
- Riveros-Burgos, C., S. Ortega-Farias, R. López-Olivari, and J. L. Chávez, 2019: Parameterization of a clumped model to directly simulate actual evapotranspiration over a superintensive drip-irrigated olive orchard. *J. Hydrometeorol.*, **20**, 935–946, <https://doi.org/10.1175/JHM-D-18-0135.1>.
- Rodrigues, T. R., G. L. Vourlitis, F. D. A. Lobo, F. B. Santanna, P. H. Arruda, and J. D. S. Nogueira, 2016: Modeling canopy conductance under contrasting seasonal conditions for a tropical savanna ecosystem of south central Mato Grosso, Brazil. *Agric. For. Meteorol.*, **218–219**, 218–229, <https://doi.org/10.1016/j.agrformet.2015.12.060>.
- Shuttleworth, W. J., and J. S. Wallace, 1985: Evaporation from sparse crops—an energy combination theory. *Quart. J. Roy. Meteor. Soc.*, **111**, 839–855, <https://doi.org/10.1002/qj.49711146910>.
- , and R. J. Gurney, 1990: The theoretical relationship between foliage temperature and canopy resistance in sparse crops. *Quart. J. Roy. Meteor. Soc.*, **116**, 497–519, <https://doi.org/10.1002/qj.497111469213>.
- Stewart, J. B., 1988: Modelling surface conductance of pine forest. *Agric. For. Meteorol.*, **43**, 19–35, [https://doi.org/10.1016/0168-1923\(88\)90003-2](https://doi.org/10.1016/0168-1923(88)90003-2).
- Sullivan, R. C., V. R. Kotamarthi, and Y. Feng, 2019: Recovering evapotranspiration trends from biased CMIP5 simulations and sensitivity to changing climate over North America. *J. Hydrometeorol.*, **20**, 1619–1633, <https://doi.org/10.1175/JHM-D-18-0259.1>.
- Tan, Z., and Coauthors, 2019: Surface conductance for evapotranspiration of tropical forests: Calculations, variations, and controls. *Agric. For. Meteorol.*, **275**, 317–328, <https://doi.org/10.1016/j.agrformet.2019.06.006>.
- Twine, T. E., and Coauthors, 2000: Correcting eddy-covariance flux underestimates over a grassland. *Agric. For. Meteorol.*, **103**, 279–300, [https://doi.org/10.1016/S0168-1923\(00\)00123-4](https://doi.org/10.1016/S0168-1923(00)00123-4).
- Tyree, M. T., A. Nardini, S. Salleo, L. Sack, and B. El Omari, 2005: The dependence of leaf hydraulic conductance on irradiance during HPFM measurements: Any role for stomatal response? *J. Exp. Bot.*, **56**, 737–744, <https://doi.org/10.1093/jxb/eri045>.
- van Dijk, A. I. J. M., and Coauthors, 2015: Rainfall interception and the couple surface water and energy balance. *Agric. For. Meteorol.*, **214–215**, 402–415, <https://doi.org/10.1016/j.agrformet.2015.09.006>.
- Walthall, C., W. Dulaney, M. Anderson, J. Norman, H. L. Fang, and S. L. Liang, 2004: A comparison of empirical and neural network approaches for estimating corn and soybean leaf area index from Landsat ETM+ imagery. *Remote Sens. Environ.*, **92**, 465–474, <https://doi.org/10.1016/j.rse.2004.06.003>.
- Wang, H., H. Guan, and C. T. Simmons, 2016: Modeling the environmental controls on tree water use at different temporal scales. *Agric. For. Meteorol.*, **225**, 24–35, <https://doi.org/10.1016/j.agrformet.2016.04.016>.
- Wang, J. F., and R. L. Bras, 2011: A model of evapotranspiration based on the theory of maximum entropy production. *Water Resour. Res.*, **47**, W03521, <https://doi.org/10.1029/2010WR009392>.
- Wang, J. M., J. X. Zhuang, W. Z. Wang, S. M. Liu, and Z. W. Xu, 2015: Assessment of uncertainties in eddy covariance flux measurement based on intensive fluxmatrix of HiWATER-MUSOEXE. *IEEE Geosci. Remote Sens. Lett.*, **12**, 259–263, <https://doi.org/10.1109/LGRS.2014.2334703>.
- Wang, K. C., and R. E. Dickinson, 2012: A review on global terrestrial evapotranspiration: Observation, modeling, climatology, and climatic variability. *Rev. Geophys.*, **50**, RG2005, <https://doi.org/10.1029/2011RG000373>.
- Wang, Y. Q., Y. J. Xiong, G. Y. Qiu, and Q. T. Zhang, 2016: Is scale really a challenge in evapotranspiration estimation? A multi-scale study in the Heihe oasis using thermal remote sensing and the three-temperature model. *Agric. For. Meteorol.*, **230–231**, 128–141, <https://doi.org/10.1016/j.agrformet.2016.03.012>.
- Xiong, Y. J., G. Y. Qiu, S. H. Zhao, and F. Tian, 2015: An evapotranspiration product for arid regions based on the three-temperature model and thermal remote sensing. *J. Hydrol.*, **530**, 392–404, <https://doi.org/10.1016/j.jhydrol.2015.09.050>.
- Xu, Z. W., and Coauthors, 2013: Intercomparison of surface energy flux measurement systems used during the HiWATER-MUSOEXE. *J. Geophys. Res. Atmos.*, **118**, 13 140–13 157, <https://doi.org/10.1002/2013JD020260>.
- Yao, Y., and Coauthors, 2017a: A simple temperature domain two-source model for estimating agricultural field surface energy fluxes from Landsat images. *J. Geophys. Res. Atmos.*, **122**, 5211–5236, <https://doi.org/10.1002/2016jd026370>.
- , and Coauthors, 2017b: Differences in estimating terrestrial water flux from three satellite-based Priestley-Taylor algorithms. *Int. J. Appl. Earth Obs. Geoinf.*, **56**, 1–12, <https://doi.org/10.1016/j.jag.2016.10.009>.
- Zhang, B. Z., Y. Liu, D. Xu, J. B. Cai, and F. S. Li, 2011: Evapotranspiration estimation based on scaling up from leaf Stomatal conductance to canopy conductance. *Agric. For. Meteorol.*, **151**, 1086–1095, <https://doi.org/10.1016/j.agrformet.2011.03.012>.
- Zhang, K., J. S. Kimball, Q. Mu, L. A. Jones, S. J. Goetz, and S. W. Running, 2009: Satellite based analysis of northern ET trends and associated changes in the regional water balance from 1983 to 2005. *J. Hydrol.*, **379**, 92–110, <https://doi.org/10.1016/j.jhydrol.2009.09.047>.
- , —, R. R. Nemani, and S. W. Running, 2010: A continuous satellite-derived global record of land surface evapotranspiration from 1983 to 2006. *Water Resour. Res.*, **46**, W09522, <https://doi.org/10.1029/2009WR008800>.
- , —, and S. W. Running, 2016: A review of remote sensing based actual evapotranspiration estimation. *Wiley Interdiscip. Rev.: Water*, **3**, 834–853, <https://doi.org/10.1002/WAT2.1168>.